

SUPERLIGHT80

The original lightweight portable x-ray generator





SUPERLIGHT80

Specification

kV (2kV steps) 50 to 80 kV	mA 20mA (effective 50mA)
Source	Single phase AC 50/60Hz 240v
Timer	0.01s to 2.00 s
Focal spot	0.8mm x 0.8mm
Filtration	2.7mm Al equivalent
Dimensions	120(w) x 300(l) x 150 (h) mm
Total weight	6.0 kg
Code	UN1006
Description	Superlight 80

The original lightweight portable x-ray generator, the Superlight 80 still combines lightweight, impressive power and a low cost

- KV range from 50 to 80 in 2kV steps
- High frequency 20mA (conventional 37.5mA) throughout the whole kV range
- DR ready. Plug your DR system in and go, no remote synchronisation box needed
- Wipe clean touch panel displays
- Digital display of kV and time
- Built in dual laser, measuring beam centre and distance. Accurate positioning every time
- Digital timer with 0.01s increments
- Ultra high frequency 120kHz inverter
- Automatic line voltage compensation, ensuring output accuracy
- Switchable audible exposure warning
- Powered by 13 amp domestic supply
- Total weight of 6kg
- Suitable for use with any of our range of stands and mountings
- 5 year extended warranty

www.veterinaryxrays.co.uk